

## Description

This double-sided tape consists of a rayon carrier layered on both sides with a rubber adhesive. The aging resistant adhesive is lined with a double-sided silicone paper.

## Carrier

Rayon

## Liner

Silicone coated paper on both sides, 80 g/m<sup>2</sup>, brown

## Adhesive

Rubber

## Area of use

This double-sided tape is extremely flexible and suitable for all material bases, including metal and wood. Limited consistency in the presence of chemicals inclined to migrate (plasticisers). Not appropriate for artificial stone floors or marble.

## Technical Data

<b>Thickness*</b> (adhesive + carrier)	200 micron	
<b>Temperature resistance***</b>	-20° C to +70° C	
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	17 N/25 mm
	after 20 min	18 N/25 mm
	after 24 h	20 N/25 mm
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 5 h	at 23° C
	4 min	at 70° C
<b>Shelf life**</b>	1 year	
<b>Application temperature</b>	> +15° C	

\* average    \*\* in original packaging, at 20°C and 50% relative humidity    \*\*\* 1h, normal climate of Central Europe

## IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.