

Description

This double-sided tape consists of a rayon carrier, layered on both sides with a rubber adhesive. The adhesive is exceptional because of its high transparency and aging resistance. The adhesive is lined with a double-sided silicone paper.

Carrier

Rayon

Liner

Silicone coated paper on both sides, 80 g/m², white

Adhesive

Rubber

Area of use

This highly rip-resistant tape is very suitable as an adhesive medium for the installation of carpet floors. This high quality carpet tape has an excellent colour stability and is therefore less likely to stain more sensitive floor surfaces. Not appropriate for artificial stone floors, marble or floor materials with a high plasticiser content.

Technical Data

Thickness* (adhesive + carrier)	220 micron	
Temperature resistance***	-20° C to +70° C	
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	18 N/25 mm
	after 20 min	20 N/25 mm
	after 24 h	22 N/25 mm
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	8 h	at 23° C
	3 min	at 70° C
Shelf life**	1 year	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research, which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.

