

Description

This double-sided tape consists of a paper tissue carrier, layered on both sides with a transparent rubber adhesive. The adhesive is lined with a double-sided silicone paper.

Carrier

paper tissue

Liner

brown paper, both sides coated with silicone

Adhesive

rubber, transparent

Area of use

This tape is suitable as an adhesive medium for smoothly surfaced materials (e. g. metal, polystyrene, glass as well as for hard PVC).

Technical Data

Thickness* (adhesive and carrier)	130 micron	
Temperature resistance	-40° C to +70° C	
Adhesive power*	27 N/25 mm	after 1min
(FINAT TM 1, on stainless steel,	30 N/25 mm	after 20min
one side covered with 50 micron polyester film)	35 N/25 mm	after 24h
Shear strength*	> 50 hours	at 23°C
(FINAT TM 8, on stainless steel,	10 minutes	at 70°C
one side covered with 50 micron polyester film)		
Shelf life	1 year	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.