

## Description

This tape consists of a closed-cell polyethylene foam coated on both sides with a modified acrylic adhesive with a high initial adhesion and high shear strength.

## Carrier

Closed-cell polyethylene foam (500 micron, black)

## Liner

Double-sided siliconised paper (90 g/m<sup>2</sup>, white)

## Adhesive

Modified acrylic

## Area of use

This tape is suitable for the permanent bonding of trims, panels, letters and emblems in the automobile industry. Due to its good UV, water and age resistance, it is suitable for external applications.

## Technical Data

<b>Thickness*</b> (foam and adhesive)	600 micron	
<b>Density*</b> (foam)	180 kg/m <sup>3</sup>	
<b>Temperature resistance***</b>	-40° C to +95° C	
<b>Loop Tack*</b> (FINAT TM 9)	30 N/25 mm	
<b>Adhesion*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	21 N/25 mm
	after 20 min	25 N/25 mm
	after 24 h	28 N/25 mm
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 300 h	at 23° C
	> 6 h	at 70° C
<b>Shelf life**</b>	2 years	
<b>Application temperature</b>	> +18° C	

\* average    \*\* in original packaging, at 20° C and 50% relative humidity    \*\*\* normal climate of Central Europe

## IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research, which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.