

Description

This tape consists of a white, closed-cell polyethylene foam coated on both sides with a modified solvent acrylate adhesive. This modified solvent acrylate adhesive possesses a high initial adhesion, even on rough and difficult substrates.

Carrier

Closed-cell polyethylene foam, white, 1000 micron

Liner

Blue paper, 90 g/m², both sides coated with silicone

Adhesive

Modified solvent acrylate

Area of use

For the installation of spray cast and extruded plastic parts such as panels, bars and ducts, as well as plexiglass mirrors for interior fit-outs and displays. For use as an adhesive medium for hooks, signs, handles and dispensers. Ideal for use in exhibition and conference fit-outs. Due to good UV, water and age resistance this product is also suitable for external applications.

Technical Data

Thickness* (foam + adhesive)	1100 micron	
Density*	67 kg/m ³	
Temperature resistance***	-40° C to +90° C	
LoopTack* (FINAT TM 9)	28 N/25 mm	
Adhesive power* (FINAT TM 1, stainless steel, one side covered with 50 micron polyester film)	after 1 min	18 N/25 mm
	after 20 min	> 18 N/25 mm, foam tear
	after 24 h	> 18 N/25 mm, foam tear
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 300 h	at 23° C
	> 6 h	at 70° C
Temperature resistance* (S.A.F.T.)	85° C	
Shelf life**	2 years	
Application temperature	> 15° C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.