

## Description

This tape consists of a black, closed-cell polyethylene foam, coated on both sides with a solvent pure acrylate adhesive. The adhesive guarantees a high final strength and is resistant towards extreme temperature, plasticisers, acids, leaches and solvents. The double-sided mounting tape is lined with a both sides siliconised PE-film.

## Carrier

Closed-cell polyethylene foam, black, 800 micron

## Liner

Both sides siliconised PE-film, 120 micron, green

## Adhesive

Solvent pure acrylate

## Area of use

Durable fixing of trims, panels, letters and emblems in the automobile industry.

## Technical Data

<b>Thickness*</b> (foam and adhesive)	900 micron
<b>Temperature resistance***</b>	-40° C to +95° C
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min: 16 N/25 mm after 20 min: 17 N/25 mm after 24 h: 20 N/25 mm
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 1000 h at 23° C > 72 h at 70° C
<b>Shelf life**</b>	2 years
<b>Application temperature</b>	> +18° C

\* average \*\* in original packaging, at 20°C and 50% relative humidity \*\*\* normal climate of Central Europe

## IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.