

Description

This double-sided tape consists of a white polyethylene foam coated on both sides with a rubber adhesive. The adhesive adheres well on non-polar substrates.

Carrier

Closed-cell polyethylene foam (1500 micron, white)

Liner

Double-sided siliconised paper (90 g/m², white)

Adhesive

Synthetic rubber

Area of use

This tape is a universal and economical product that bonds well to rough surfaces, and is suitable for bonding plates, displays and household accessories in commercial and industrial applications.

Technical Data

Thickness* (foam and adhesive)	1600 micron	
Density*	58 kg/m ³	
Temperature resistance***	-30° C to +70° C	
Loop Tack* (FINAT TM 9)	28 N/25 mm	
Adhesion* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min	> 18 N/25 mm
	after 20 min	> 18 N/25 mm, foam tear
	after 24 h	> 18 N/25 mm, foam tear
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 500 h	at 23° C
Shelf life**	1 year	
Application temperature	> +15° C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research, which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.