

Description

This mounting tape consists of a white, closed-cell polyethylene foam coated on both sides with a rubber adhesive. It adheres well among other things on apolar substrates. The double-sided mounting tape is lined with a white silicone paper.

Carrier

Closed-cell polyethylene foam, white, 800 micron

Liner

Both sides siliconised paper, 90 g/m², white

Adhesive

Rubber

Area of use

For fixing of boards, displays and for a variety of household applications. A universal and economical product.

Technical Data

| | | |
|--|----------------------|-----------------------|
| Thickness* (foam and adhesive) | 900 micron | |
| Density* | 95 kg/m ³ | |
| Temperature resistance*** | -30° C to +70° C | |
| LoopTack* (FINAT TM 9) | 28 N/25 mm | |
| Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 microns polyester film) | after 1 min | 18 N/25 mm |
| | after 20 min | 36 N/25 mm, foam tear |
| | after 24 h | 36 N/25 mm, foam tear |
| Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 microns polyester film) | > 500 h | at 23° C |
| Shelf life** | 1 year | |
| Application temperature | > +15° C | |

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research, which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.

