

## Description

This mounting tape consists of black, closed-cell polyethylene foam, which is coated on the open side with a permanent, modified acrylate adhesive. The modified acrylate adhesive has very high shear strength and very high initial adhesion as well as very good adhesion to low energy surfaces. The covered side is coated with a solvent pure acrylate adhesive, which guarantees an excellent temperature resistance, high final strength and resistance to plasticisers, acids, leaches and solvents. To allow an easy release the covered side is equipped with a PET-interlayer.

## Carrier

Closed-cell polyethylene foam  
Interlayer: polyester film

## Liner

White paper, both sides coated with silicone, 90 g/m<sup>2</sup>

## Adhesive

Polyacrylate adhesive

## Area of use

Developed for the use in optical laboratories for the adhesion of water-repellent materials.

## Technical Data

<b>Thickness*</b> (adhesive + foam)	ca. 1.0 mm
<b>Temperature resistance***</b>	-40° C to +80° C
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	covered side: after 1 min: 16 N/25 mm after 20 min: 18 N/25 mm after 24 h: > 18 N/25 mm  open side: after 1 min: > 30 N/25 mm after 20 min: > 30 N/25 mm after 24 h: > 30 N/25 mm
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	covered side: at 23° C: > 1000 hours at 70° C: > 72 hours  open side: at 23° C: > 300 hours at 70° C: 1 hour
<b>Shelf life**</b>	2 years
<b>Application temperature</b>	> +15° C

\* average \*\* in original packaging, at 20°C and 50% relative humidity \*\*\* 1h, normal climate of Central Europe

## IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research, which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.