

## Description

ORACAL® Decorative Window Film series are PET-based interior design films for application on flat glass surfaces.

## Technical Data

<b>Thickness</b> <sup>(1)</sup> (without liner and adhesive)	0,038 mm or 0,050 mm (see product description)
<b>Adhesive</b>	Polyacrylate
<b>Release Liner</b>	Silicone-coated polyester
<b>Shelf life</b> <sup>(2)</sup>	2 years
<b>Application temperature</b>	> +10 °C
<b>Proposed application technique</b>	Wet application process
<b>Maximum service life</b> <sup>(3)</sup> by specialist application and with proper maintenance and care.	5 years (interior)

<sup>(1)</sup> average    <sup>(2)</sup> in original packaging, at 20 °C and 50% relative humidity    <sup>(3)</sup> Applies for interior application. For more information, please visit: [www.orafol.com/gp/europe/en/support](http://www.orafol.com/gp/europe/en/support)

**Product descriptions**

<b>ORACAL®</b>	<b>Pattern</b>	<b>Thickness</b>
<b>W001</b>	White Stripes of 4mm	38 µm
<b>W002</b>	White stripes of 10mm	38 µm
<b>W004</b>	White stripes of 30mm	38 µm
<b>W014</b>	White Squares of 20mm	38 µm
<b>W018</b>	White Cocoon design	38 µm
<b>UV05</b>	Frosted stripes of 35mm	38 µm
<b>UV10</b>	Frosted stripes of 5mm and 35mm	38 µm
<b>UV11</b>	Frosted Squares of 44mm	38 µm
<b>G002</b>	Grey Stripes of 10mm	38 µm
<b>WM20</b>	White Matt	38 µm
<b>DX01</b>	Vertical white lines	50 µm
<b>DX02</b>	White Grids	50 µm
<b>DX03</b>	White circles of 3mm diameter	50 µm
<b>DX04</b>	Gradient design with white circles	50 µm
<b>DX05</b>	Gradient design with vertical lines of white dots	50 µm
<b>DX06</b>	White & grey quadrilaterals with diamond appearance	50 µm

**Note**

The above information is based on our present knowledge and practical experience. The information is given without any guarantee or agreement with regards to the quality or properties of the material. It does not constitute a warranty of any certain quality, properties and/or service life concerning the ORAFOL® films.

For application of ORAFOL® films (wrapping and removal) as well as for maintenance and use, please refer to our documents Processing Guidelines and Maintenance and Usage Terms. If our guidelines are not followed, please be advised that in particular the maximum service life information, stated as based on our experience, does not apply. If the Processing Guidelines and Maintenance and Usage Terms are not complied with, any warranty and liability is excluded.

The batch traceability according to ISO 9001 is possible on the basis of the roll number.

**IMPORTANT NOTICE**

All ORACAL® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORACAL® products is based upon research which the company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORACAL® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORACAL® is a registered trademark of ORAFOL Europe GmbH.

