

Description

This transfer tape consists of a modified water soluble acrylate adhesive. It has a good tack and an excellent thermal resistance.

Carrier

Without carrier

Liner

Siliconised paper on both sides, 90 g/m², white

Adhesive

Modified acrylate, water soluble, green

Area of use

Water soluble splicing tape without carrier and with high toughness. Appropriate for extremely thin splicing in LWC paper applications.

The used adhesive RA3 meets the demands of the Code of Federal Regulations, Food and Drugs (FDA), 21 CFR Ch. I (April 1, 2008 edition), § 175.105.

Technical Data

Thickness* (adhesive + carrier)	50 micron
Temperature resistance***	up to +200° C, momentary up to +230° C
LoopTack* (FINAT TM 9)	10 N/25 mm
Adhesive power* (FINAT TM 1, on copying paper, one side covered with 50 micron polyester film)	after 1 min: 8 N/25 mm after 20 min: 11 N/25 mm
Shear strength* (S.A.F.T. Test from 23° C up to 230° C)	90 min/+230° C
Repulpability (according to TAPPI UM 213)	meets requirements
Shelf life**	12 months, in closed original packing

* average ** in original packaging, at 20° C and 50% relative humidity *** normal climate of Central Europe

IMPORTANT NOTICE

All ORAFIX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFIX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFIX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFIX® is a registered trademark of ORAFOL Europe GmbH.

