

Description

This double-sided adhesive tape consists of a repulpable, easily splittable paper carrier coated on both sides with a modified acrylic adhesive. The adhesive RA4 has strong tack and excellent thermal resistance and fulfils the requirements of the Code of Federal Regulations, Food and Drugs (FDA), 21 CFR Ch. I, § 175.105.

Carrier

Repulpable splittable paper (white)

Liner

Double-sided siliconised paper (90 g/m², white)

Adhesive

Water-soluble modified acrylic, colourless

Area of use

Water repulpable splicing tape for commercial and industrial applications with high thermal resistance for core starting and roll closing of thick and bend-proof paper / board.

Technical Data

Thickness* (adhesive + carrier)	200 micron
Temperature resistance***	up to +200° C, short term up to +230° C
Loop Tack* (FINAT TM 9)	4 N/25 mm
Adhesion* (FINAT TM 1, on copying paper, one side covered with paper)	after 1 min 5 N/25 mm after 20 min >5 N/25 mm, splitting
Shear strength* (S.A.F.T. test from 23° C up to 230° C)	90 min/+230° C
Repulpability (according to TAPPI UM 213)	meets requirements
Shelf life**	12 months in closed original packing

* average ** in original packaging, at 20° C and 50% relative humidity *** normal climate of Central Europe

IMPORTANT NOTICE

All ORAFIX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFIX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFIX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFIX® is a registered trademark of ORAFOL Europe GmbH.