

### Description

This single-sided tape consists of polyester film carrier coated with silicone adhesive. The adhesive has high shear strength and high temperature, aging and plasticisers resistant. The adhesive shows high bond strength on siliconised surfaces.

### Carrier

Polyester film (23 micron, transparent, single-sided siliconised)

### Liner

Hard PVC film (45 micron, white, creped)

### Adhesive

Silicone, transparent

### Area of use

This tape is ideal as an adhesive in industrial and commercial applications, for bonding siliconised paper and films as well as for core starting or roll closing / end tabbing of siliconised materials. The backside siliconisation enables the use as splicing tape in coating and converting applications.

### Technical Data

<b>Thickness*</b> (adhesive and carrier)	60 micron		
<b>Temperature resistance***</b>	-40° C to +180° C, short term up to +200° C		
<b>Loop Tack*</b> (FINAT TM 9, on stainless steel)	10 N/25 mm		
<b>Adhesion*</b> (FINAT TM 1, on stainless steel)	9 N/25 mm	after 1 min	
	10 N/25 mm	after 20 min	
	12 N/25 mm	after 24 h	
<b>Shear strength*</b> (FINAT TM 8, on stainless steel)	> 72 h	at 23° C	
	> 1 h	at 70° C	
<b>Temperature resistance*</b> (S.A.F.T.)	120° C		
<b>Shelf life**</b>	6 months		
<b>Application temperature</b>	> +15° C		

\* average

\*\* in original packaging, at 20°C and 50% relative humidity

\*\*\* 1h, normal climate of Central Europe

### IMPORTANT NOTICE

All ORAFIX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFIX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFIX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFIX® is a registered trademark of ORAFOL Europe GmbH.