

Application

Double-sided filmic tape for photopolymer or rubber plate mounting on sleeves or print cylinders for flexography, letterpress and label printing

Construction

Thickness without liner*	Approx. 100 micron (4 mil)
Liner	Creped PP film, 80 micron, brown
Adhesive, closed side	Natural rubber
Carrier	PET film, transparent
Adhesive, open side	Natural rubber

* average

Technical Properties

180° peel* [N/25 mm], FINAT TM 1, 20 min. dwell time	8
90° peel* [N/25 mm], FINAT TM 2, 20 min. dwell time	7
Dynamic shear*	180 N/625 mm ²
Temperature resistance*	+60° C

* average

Product Properties

- 100 micron (4 mil) plate mounting tape
- High dimensional stability
- Firm PET carrier with high thickness accuracy
- High tack natural rubber adhesive for a secure bond between plate and cylinder
- Clean and easy removal
- Creped PP liner enables mounting without air bubbles

IMPORTANT NOTICE

All ORAFLEX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFLEX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFLEX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFLEX® is a registered trademark of ORAFOL Europe GmbH.

