

## Application

Medium hard, double coated foam tape with 380 micron (15 mil) application thickness and differential acrylic adhesives on each side. For mounting of thin photopolymer plates up to 1.7 mm (0.067") on composite and urethane sleeves or print cylinders in the high-quality label printing industry (narrow- and mid web process).

## Construction

<b>Thickness without liner*</b>	approx. 430 micron (17 mil)
<b>Liner</b>	embossed PP film, 110 micron, white
<b>Adhesive, closed side</b>	acrylic
<b>Carrier</b>	medium hard PE foam, white on plate side
<b>Adhesive, open side</b>	acrylic


\* average

## Product Properties


- Medium hard plate mounting tape
- 380 micron (17 mil) application thickness
- Hardness grade "medium" indicated by the white colour code
- Minimum thickness tolerances
- Differential acrylate with lower adhesion to plate for a secure mounting without edge-lifting
- Easy and clean demounting
- Easy repositioning
- Embossed liner enables plate mounting without air entrapments

## Application fields

- especially suitable for fine lines, halftones and process printing
- combination of solid and screen



ORAFLEX® 11522  
soft



ORAFLEX® 11552  
medium



ORAFLEX® 11582  
firm

## IMPORTANT NOTICE

All ORAFLEX® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFLEX® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFLEX® products and the continuing development of new applications, the purchaser should carefully consider the suitability and

performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAFLEX® is a registered trademark of ORAFOL Europe GmbH.