

Description

Cleaning and care products especially developed for maintenance of vehicles wrapped with glossy car wrapping films from ORAFOL.

	Intensive cleaner – glossy	Long lasting seal – glossy
Description	Intensive cleaner especially developed for maintenance of vehicles wrapped with glossy car wrapping films.	Extremely easy-to-process sealing with carnauba wax and synthetic waxes.
Application	Spray directly onto the contaminated area and leave it on for 1-2 minutes. If necessary, intensify the process with a cleaning brush. Rinse off thoroughly with clear water.	Apply long-lasting seal onto an application sponge or a polishing pad. Process crosswise onto the degreased film surface. Let it air dry for a minute. Afterwards wipe off with a soft microfiber cloth without applying pressure. Long-lasting seal does not dry completely before polishing, therefore it is not time-critical or temperature-critical in application. After 12 hours the maximum sealing level is achieved.
Notes	Do not apply onto hot coatings, films or rims, and do not let it dry out. Before use check for material compatibility in a concealed area.	Shake well before use. Protect product from freezing!
Ingredients (according to regulation (EG) 648/2004)	Nonionic surfactants less than 5%, cationic surfactants less than 5%, amphoteric surfactants less than 5%, chelating agents (GLDA) less than 5%, phosphonates less than 5%, fragrances (free of allergens 2003/15/EU), dye, additional information: silicates.	Aliphatic hydrocarbons 15-30%, nonionic surfactants less than 5%, preservatives (Phenoxyethanol, Laurylamine, Dipropylendiamine, Butylbenzothiazolinone, fragrances, dye, additional information: silicone oil, waxes, synth. polymers, thickeners.
Shelf life	3 years*	3 years*
Application temperature	> 10° C, but not in direct sunlight, not on hot surfaces.	> 10° C, but not in direct sunlight, not on hot surfaces.

* in original packaging, at 0 – 35° C

Important to note

The above information is based upon our present knowledge and practical experience. The information is given without any guarantee or agreement with regards to the quality or properties of the material. It does not constitute a warranty of any certain quality, properties and/or service life concerning the ORAFOL® products.

Please note that by nature films are more sensitive than lacquers. Therefore, films must be treated and maintained with the greatest care. For application of ORAFOL colour films (wrapping and removal) as well as for maintenance and use, please refer to our documents 'Processing Guidelines' and 'Maintenance and Usage Terms' (both documents are available in pdf format to download: www.orafol.com/gp/europe/en/support). If our guidelines are not followed, please be advised that in particular the maximum service life information, stated as based on our experience, does not apply. Further information about the expected maximum service life is found in the Processing Guidelines (see no. 2 there). If the processing guidelines and maintenance and usage terms are not complied with, any warranty and liability is excluded.

Please contact a professional workshop or ORAFOL's customer support if you have further questions.

IMPORTANT NOTICE

All ORAFOL® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAFOL® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAFOL® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

