Description

Polymeric PVC film with glossy, semi-glossy or matt surface and a high level of UV protection.

Release Paper

Silicone coated paper, white, 90 g/m²

Adhesive

Solvent polyacrylate, permanent

Area of use

For the protection of digitally printed large format pictures in indoor and outdoor applications.

Technical Data

Thickness (1) (without paper and adhesive)	75 micron
Temperature resistance (2)	adhered to aluminium, -50° C to +90° C, no variation
Resistance to solvents and chemicals	At room temperature, 72h after adhesion to aluminium, resistant to water, cleaning agents, alcohol and aliphatic solvents
Adhesive power (1) (FINAT TM 1, after 24h, stainless steel)	12 N/25 mm
Tensile strength ⁽¹⁾ (DIN EN ISO 527)	Along: > 19 MPa Across: > 19 MPa
Elongation at break (1) (DIN EN ISO 527)	Along: > 130% Across: > 150%
Shelf life (3)	2 years
Application temperature	> +8° C
Maximum service life by specialist application Applies for vertical outdoor exposure (4)	5 years

Note

Due to the diversity of prints and printing techniques, the user should test the suitability of ORAGUARD® laminating films for the specific print purpose, prior to use. Furthermore, the application information published by ORAFOL must be followed.

IMPORTANT NOTICE

All ORAGUARD® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAGUARD® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAGUARD® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice. ORAGUARD® is a registered trademark of ORAFOL Europe GmbH.

