# **Description**

Highly transparent, PVC-free polypropylene-based laminating film with effective UV protection. Available with a glossy surface.

## **Release Paper**

Silicone coated paper, white, 90 g/m<sup>2</sup>

## **Adhesive**

Polyacrylate, permanent

#### Area of use

For the protection of large digitally printed formats for indoor and short-term outdoor use. Specially recommended for use in combination with the PVC-free digital printing films ORAJET® 3172X, 3174 and 3174X.

### **Technical Data**

0.060 mm
0,060 mm
Adhered to aluminium, -40° C to +80° C, no variation
At room temperature, 72h after adhesion to aluminium, resistant to water, cleaning agents, alcohol and aliphatic solvents
12 N/25 mm
Along: min. 20 MPa Across: min. 20 MPa
Along: min. 300% Across: min. 350%
2 years
> +10° C
3 years

### **Note**

Due to the diversity of prints and printing techniques, the user should test the suitability of ORAGUARD® laminating films for the specific print purpose, prior to use. Furthermore the application information published by ORAFOL must be followed.

# **IMPORTANT NOTICE**

All ORAGUARD® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAGUARD® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAGUARD® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAGUARD® is a registered trademark of ORAFOL Europe GmbH.

