Description

Premium cast PVC film with the highest level of UV protection. Glossy surface.

Release Paper

Silicone coated paper, white, 90 g/m²

Adhesive

Solvent polyacrylate, permanent

Area of use

For the protection of digitally printed large format images in indoor and outdoor applications. Especially recommended on UV digital printings.

Technical Data

0,050 mm
Adhered to aluminium, -50° C to +110° C, no variation
Adhered to aluminium, after 100h/23° C, no variation
At room temperature, 72h after adhesion to aluminium, resistant to water, cleaning agents, alcohol and aliphatic solvents
14 N/25 mm
Along: min. 19 MPa Across: min. 19 MPa
Along: min. 120% Across: min. 120%
2 years
> +8° C
8 years
umidity *** normal climate of Central Europe

Note

Due to the diversity of prints and printing techniques, the user should test the suitability of ORAGUARD® laminating films for the specific print purpose, prior to use. Furthermore the application information published by ORAFOL must be followed.

IMPORTANT NOTICE

All ORAGUARD® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAGUARD® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAGUARD® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice. ORAGUARD® is a registered trademark of ORAFOL Europe GmbH.

