

Description

White coated paper (120 g/m²) with a special matt inkjet coating on one side.

Release Paper

Silicone coated paper, 85 g/m²

Adhesive

Polyacrylate, permanent, transparent

Area of use

For the inexpensive production of large format prints for indoor short-term decoration.

Printing Method

Water-based inkjet printing, dye and pigmented inks

Recommended printers

Refer to www.orafol.com for recommended inkjet printers

Technical Data

Thickness* (without paper and adhesive)	100 micron
Temperature resistance	Adhered to aluminium, -20° C to +60° C, no variation
Adhesive power* (FINAT TM 1, after 24h, stainless steel)	16 N/25 mm (tear of the paper)
Shelf life**	1 year
Application temperature	> +10° C

* average ** in original packaging, at 20° C and 50% relative humidity ***short-term stress

Note

After printing, the ink must be allowed to thoroughly dry, in order to avoid any issues when later combined with the laminate. Surfaces to which the material will be applied must be thoroughly cleaned and free from dust, grease or any contamination which could affect the adhesion of the material. Freshly lacquered or painted surfaces should be allowed to dry for at least three weeks and to completely cure. The compatibility of the selected lacquers and paints should be tested by the user, prior to the application of the material. Furthermore the application information published by ORAFOL must be considered.

IMPORTANT NOTICE

All ORAJET® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAJET® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAJET® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAJET® is a registered trademark of ORAFOL® Europe GmbH.