

Description

This double-sided tape consists of a paper tissue carrier coated on both sides with a synthetic rubber adhesive and lined with siliconised paper. This adhesive has excellent bonding characteristics.

Carrier

Paper tissue (12,7 g/m²)

Liner

Double-sided siliconised paper, (80 g/m², yellow)

Adhesive

Synthetic rubber

Area of use

This tape is suitable for bonding a variety of materials in industrial and commercial applications. It has limited resistance to plasticisers and other readily migrating chemicals.

Technical Data

Thickness* (adhesive + carrier)	90 micron	
Temperature resistance***	-40 °C to +70 °C	
Loop Tack* (FINAT TM 9)	12 N/25 mm	
Adhesion*	13 N/25 mm	after 1 min
(FINAT TM 1, on stainless steel,	14 N/25 mm	after 20 min
one side covered with 50 micron polyester film)	15 N/25 mm	after 24 h
Shear strength*	> 72 h	at 23 °C
(FINAT TM 8, on stainless steel,	3 min	at 70 °C
one side covered with 50 micron polyester film)		
Temperature resistance* (S.A.F.T.)	75 °C	
Shelf life**	1 year	
Application temperature	> +15 °C	

* average ** in original packaging, at 20°C and 50% relative humidity *** 1h, normal climate of Central Europe

Available Liner versions

09* Double-sided siliconised paper (90 g/m², white)

* MOQ upon request.

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser

should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.