

## Description

This transfer tape consists of a high performance modified solvent acrylate adhesive with a good resistance to ultraviolet radiation, temperatures, chemicals, solvents and humidity. Its transfer adhesive is extremely durable on metal, varnish and high energy plastics surfaces and is very durable on low energy surfaces.

## Carrier

Without carrier

## Liner

both sides siliconised PE paper, 100 g/m<sup>2</sup>, brown

## Adhesive

modified solvent acrylate

## Area of use

Ideal as an adhesive medium for foams and materials that require a very high adhesive strength. For adhesion to smooth and slightly rough surfaces with high initial adhesion. Especially recommended for low energy plastic surfaces. The Transfer Tape is certified according to UL 969.

## Technical Data

<b>Thickness*</b> (adhesive without liner)	60 micron
<b>Temperature resistance***</b>	-40° C to +150° C, momentary up to +190° C
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	23 N/25 mm after 1 min 25 N/25 mm after 20 min 27 N/25 mm after 24 h
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 500 h at 23° C > 10 h at 70° C
<b>Shelf life**</b>	2 years
<b>Application temperature</b>	> +15° C

\* average    \*\* in original packaging, at 20° C and 50% relative humidity    \*\*\* normal climate of Central Europe

## IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.

